

Soil boring: BH5

| | | | |
|---------------------|---------------------------------|--------------------------------|--------------------------|
| Project | 0051052 | Drilling method | Continuous coring |
| Client | AMI Italia S.r.l. | Drilling company | Eurogeo |
| Site | Castellanza (VA - Italy) | Casing diameter (mm) | 101 |
| Date | 13/06/2006 | Pipe diameter (") | - |
| Logger | CHA | Depth (m bgl) | 10 |
| X Coordinate | | Ground level (m asl) | 220 |
| Y Coordinate | | Well-head level (m asl) | - |



| Depth | Lithology | Description | Notes | ppm VOC | Samples |
|-------|-----------|--|--------------------------------|---------|---------|
| 0.0 | | Fore-excavation (slightly gravelly sands with fragments of tarmac) | | | |
| | | slightly gravelly sands | brown coloured | | |
| | | gravelly sands with pebbles | | | 3.2 |
| | | | | 0 | |
| | | | | 0 | |
| 5.0 | | sandy gravel with pebbles | brown coloured | | |
| | | slightly clayey sands with gravels and pebbles | saturated soil; gray coloured | | |
| | | | | 0 | |
| | | slightly clayey sands with gravels and pebbles | saturated soil; brown coloured | | |
| | | | | 0 | |
| | | slightly clayey sands with gravels | saturated soil; gray coloured | | |
| | | | | 0 | |
| 10.0 | | | | | 9.8 |