


# Soil boring: BH2

<b>Project</b>	<b>0051052</b>	<b>Drilling method</b>	<b>Continuous coring</b>
<b>Client</b>	<b>AMI Italia S.r.l.</b>	<b>Drilling company</b>	<b>Eurogeo</b>
<b>Site</b>	<b>Castellanza (VA - Italy)</b>	<b>Casing diameter (mm)</b>	<b>101</b>
<b>Date</b>	<b>13/06/2006</b>	<b>Pipe diameter (")</b>	-
<b>Logger</b>	<b>CHA</b>	<b>Depth (m bgl)</b>	<b>10</b>
<b>X Coordinate</b>		<b>Ground level (m asl)</b>	<b>221</b>
<b>Y Coordinate</b>		<b>Well-head level (m asl)</b>	-



**ERM**

**ERM Italia s.r.l.**

Via San Gregorio 38  
20124 Milano - I  
tel. +39/02/674401  
fax +39/02/67078382

Via Galilei 45  
00185 Roma - I  
tel. +39/06/77401411  
fax +39/06/77250300  
info.italy@erm.com

Depth	Lithology	Description	Notes	ppm VOC	Samples
0.0		Fore-excavation (sands and gravels with pebbles)	brown coloured		
		sands and gravels with pebbles	brown coloured	0	
		pebbles			3.2
		slightly clayey sands with gravels and pebbles		0	
		clayey sands with gravels and pebbles	saturated soil; brown coloured	0	
5.0		gravels with sands and pebbles	unsaturated soil; gray-brown coloured	0	
		clayey sands with gravels and pebbles	unsaturated soil; brown coloured	0	
		sands and gravels with pebbles		0	9.5
10.0					